



CORD KING CS20-40

CONTACT US FOR PRICING AND TO CUSTOMIZE YOUR MACHINE TODAY!



SPECIFICATIONS:

- 99 HP JCB Turbo Diesel Engine
Tier 4
- 48" carbide tooth slasher saw
- 34 ton splitter force
- 6- or 8-way fixed splitting wedge
- 20' infeed with 4-leg live deck
- Hydraulic log stop (adjustable
12-24" length)
- Operator safety cage with roof
and deluxe seat
- Automatic clamping
- Fuel capacity: 40-gallon fuel tank
- Hydraulic Reservoir Capacity:
120 US gallons
- Hydraulic Oil Cooler standard:
48,000 BTU/hr
- 14k lbs tandem axles with electric
brakes and running lights
- Pintle Hitch

PERFORMANCE:

- Production Rate: 6 to 8 full cords/hr
- Cycle Time (cut & split): every 3
seconds
- Max Log Diameter: 20"
- Max Log Length: 40'
(butt on the deck)
- Estimated Fuel Consumption:
2.5 GPH
- Weight: 14,000 lbs
- Transport Dimensions:
8'-6" wide, 12' high

OPTIONAL EQUIPMENT:

- 42-ton splitter (required for 10- or
12-way wedge)
- 58-ton splitter (required for 16- to
28-way wedge)
- Hydraulically adjustable wedge
- Quick-change hydraulically
adjustable box wedge, 10 to 28-way
split (28-way to split wood small
enough for packaging)
- Hydraulic Folding Log Deck
- Extra live deck legs, dual drive
available
- Heated operators cab
- Air conditioning (hydraulically driven
or 120V plug in)
- 24' to 40' stand alone offloading
conveyor (radial stacking)
- 12' or 16' integrated offloading
conveyor
- Overhead log grapple assist (crooked
wood)
- Trap doors for last piece assist (easy
end-of-log cutting)
- Saw log deck for cutting saw logs and
firewood