



CORD KING M18-20R

CONTACT US FOR PRICING AND TO CUSTOMIZE YOUR MACHINE TODAY!



STANDARD EQUIPMENT:

- 35 HP Briggs and Stratton Vanguard Twin Gas Powered (with 3-year warranty)
- Hydraulic-driven 404 harvester bar and chain with pressure relief system
- Electric bar oiler system with large 1 ½ gallon capacity
- Electric start with low oil pressure shut-down
- Splitter Force 24 ton
- 4- or 6-way fixed splitting wedge
- Automatic clamping
- Adjustable log length gauge
- 12' long Infeed Conveyor with continuous chain drive feeding
- Available with standard 2-leg manual folding live deck (6') or 2-leg log lifting system with double 2" hydraulic cylinders
- Lexan safety screen for excellent visibility
- Firewood Cleanout Grate
- Fuel Capacity: 10-gallon fuel tank
- Hydraulic Reservoir Capacity: 40 gallons
- 5k lbs axel with electric brakes and running lights
- 2 5/16" Ball Hitch

PERFORMANCE:

- Production Rate: up to 1.5-2 full cords/hr
- Cycle Time (cut and split): every 4 seconds
- Maximum Log Diameter: 20"
- Maximum Log Length: 20' (butt on the deck)
- Estimated Fuel Consumption: 1 – 1.5 GPH
- Weight: 5,800 lbs
- Transport Dimensions: 7'-0" wide, 23'-0" long, 12'-8" high

OPTIONAL EQUIPMENT:

- 29-ton splitter
- 34-ton splitter (required for 12 and 16-way wedge)
- Hydraulic Folding Log Deck
- Extended live deck (8') with bearing upgrade
- 4-, 6-, 8-, 12- or 16-way hydraulically adjustable wedge
- Turbo split with Hydraulic Oil Cooler
- Hydraulic log stop (adjustable 12-24" length)
- Extended infeed conveyor (to 16') with tandem axle
- Extra live deck legs, dual drive available
- Operator platform with deluxe seat
- Operator safety cage or operator canopy (roof)
- 16' to 40' standalone offloading conveyor (radial stacking)
- 12' or 16' integrated offloading conveyor
- Auto-split (1 button complete splitting cycle)
- Available with tractor PTO-Drive
- Available with a 3-phase electric motor option